



FLOOR

ALESSI™
GLAZED PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Cover and above photo features Dorato 13 x 13 field tile in a brick-joint pattern on the floor.

Embrace the Warm Look of Stone

Emulating look of stone, Alessi™ enriches any space. Its warm color palette is quintessential for creating a sophisticated neutral backdrop. Alessi's sleek look and versatile sizes make it an ideal residential floor tile.

- IDEAL DESIGN
 - Sophisticated, inviting design
 - Quintessential residential floor tile
- BEAUTY AND FUNCTION
 - Warm, neutral color palette
 - Available with coordinating trim



MADE IN THE U.S.A.



REVEAL IMAGING®



TRU-EDGE

All or select items within this series are made in the USA. For more information, visit daltile.com/Alessi.

CERTIFIED PORCELAIN TILE
© 5% or less water absorption

FIELD TILE



CREMA AL05



DORATO AL06




NOCE AL07

FLOOR

ALESSI™

GLAZED PORCELAIN

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	20 x 20 Field Tile	(19-1/2" x 19-1/2") (49.36 cm x 49.36 cm)	5/16"	15.72	6
	13 x 13 Field Tile	(13" x 13") (32.80 cm x 32.80 cm)	5/16"	14.95	13
	12 x 24 Field Tile	(11-5/8" x 23-5/8") (29.56 cm x 59.44 cm)	3/8"	15.12	8

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.


OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	P-43E9	3 x 13	30

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

Note: 3 x 12 or 3 x 24 bullnose available by special order with extended lead time. Contact your sales representative for more information.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 High (V3)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3

For additional information, visit daltile.com/information/TestResults.

NOTES

Manufacturer Warning: These tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DAL TILE.COM



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (8/16)