



FLOOR | WALL

MARBLE FALLS™

GLAZED CERAMIC with REVEAL IMAGING®

 **daltile**®
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature White Water in 18 x 18 field tile on the floor with 10 x 14 wall tile and 2 x 4 brick-joint mosaic on wall.

Compelling Alternative to Natural Marble Stone

The classic elegance of Marble Falls™ glazed ceramic tile rivals the exquisite details found in nature. Produced with Reveal Imaging® technology, the crisp graphics, wide pattern variation and delicate veining will draw the eye again and again. Glossy floor, wall and mosaic tiles are offered in a neutral color palette in a variety of sizes. Durability and ease of maintenance make this an easy product to love. Whether the style is traditional or modern, Marble Falls will create a luxe and beautiful view.

- MODERN VERSATILITY & NEUTRAL COLORS
 - Timeless design and a neutral palette create a versatile look
- REFINED STYLE
 - Floor, wall and mosaic formats offer complete design solutions
 - Elegant graphics create a sleek and styled look
- SIMPLE UPKEEP
 - Durability and easy maintenance make this tile an outstanding choice



**POST-CONSUMER
RECYCLED MATERIALS**



**PRE-CONSUMER
RECYCLED MATERIALS**



REVEAL IMAGING®

MARBLE FALLS™

GLAZED CERAMIC with REVEAL IMAGING®

FIELD TILE



WHITE WATER MA40



CRYSTAL SANDS MA41



HIGHLAND BEIGE MA42



GRAY PEARL MA43

WALL TILE



WHITE WATER MA40



CRYSTAL SANDS MA41



HIGHLAND BEIGE MA42



GRAY PEARL MA43

MOSAICS



WHITE WATER MA40



CRYSTAL SANDS MA41



HIGHLAND BEIGE MA42








GRAY PEARL MA43








MARBLE FALLS™

GLAZED CERAMIC with REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	18 x 18 Floor Tile	(17-3/4" x 17-3/4") (45.20 cm x 45.20 cm)	5/16"	18.00	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	11.00	11
	10 x 14 Wall Tile	(9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	4-1/4 x 8-1/2 Wall Tile	(4-1/4" x 8-9/16") (10.88 cm x 21.82 cm)	5/16"	10.50	42
	2 x 4 Brick-joint Mosaic (Dot-mounted on 12" x 12" Sheet)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4"	9.96	12

TRIM

	Type	Number	Size
	Floor Bullnose*	P-43C9	3 x 12
	Wall Bullnose	S-4310	3 x 10
	Wall Bullnose Corner	SN-4310	3 x 3
	Wall Bullnose	S-4849 (4" side)	4-1/4 x 8-1/2
	Wall Bullnose	S-4489 (8" side)	4-1/4 x 8-1/2
	Wall Bullnose Corner Right	SCR-4489	4-1/4 x 8-1/2
	Wall Bullnose Corner Left	SCL-4489	4-1/4 x 8-1/2

* Floor bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor : 3/16" Wall : 1/16" Mosaic : 1/8"	 High (V3)

FLOOR APPLICATIONS

(Excludes Wall Tile)	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.daltile.com/dcof.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	
Pool Linings	✓*

APPLICATION NOTES:

* Mosaics only

Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

TEST RESULTS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs.	120-230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	6.0	4.0-6.0	6.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	3	N/A	3

For additional information, visit daltile.com/information/TestResults.

NOTES

Manufacturer Warning: These tiles have a dynamic coefficient of friction less than 0.42 as measured by the DCOF Acutest method. Tiles with DCOF Acutest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall or personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at: daltile.com/Factors



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DAL TILE.COM



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (4/16)