



FLOOR

DIGNITARY™

STONE ATTACHÉ™ COLLECTION – COLORBODY™ PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Cover photo features Dignitary™ Superior Taupe 24 x 48 on the floor, Superior Taupe 12 x 24 on the left wall, Luminary White 12 x 24 on the right wall, and Superior Taupe abstract mosaic on the shower wall. Above photo features Dignitary™ Superior Taupe 24 x 48 on the floor and Luminary White 12 x 24 on the wall.

Ageless and Innovative – the Dignitary™ Series

The imaginative Dignitary Series provides depth on surfaces as it replicates French limestone embedded with fossil layers and natural veins. Beautiful in any setting, this outstanding ColorBody™ porcelain tile is equally suited to traditional or contemporary styles, bringing ageless dimension to every application. An array of colors in unpolished finish are available in three large-format sizes and a coordinating mosaic. Polished and textured finishes, as well as a 2 cm thickness, are also available in select sizes.

- REIMAGINING A CLASSIC
 - Small fossils and veining replicate the look of French limestone that has stood the test of time
 - Six rich neutral colors appeal to contemporary tastes
 - 2 cm thick tile available in 24 x 24 size and three colors
- AGELESS BEAUTY ANYWHERE
 - Three finishes offer the ability to stretch designs from floors to walls, indoors, and out
 - Three large-format sizes plus an abstract mosaic all provide dimensional depth

 **PRE-CONSUMER RECYCLED MATERIALS**

 **MADE IN THE U.S.A.**

 **TRU-EDGE™**

All or select items within this series meet the requirements for these qualifications. For more information visit daltile.com.

USAGE

Floors	Walls	Countertops
F	W	C

 **CERTIFIED RECELAIN™ TILE**
0.5% or less water absorption

FLOOR TILE

Available in Unpolished, Light Polished & Textured



LUMINARY WHITE DR07*



NOTABLE BEIGE DR09*



EMINENCE GREY DR10



SUPERIOR TAUPE DR08*



HERALD BROWN DR12



GOVERNOR BLACK DR11

ABSTRACT MOSAIC


Available in Unpolished only



LUMINARY WHITE DR07




NOTABLE BEIGE DR09




EMINENCE GREY DR10



SUPERIOR TAUPE DR08



HERALD BROWN DR12



GOVERNOR BLACK DR11

* Available in 2 cm thickness in 24 x 24 size

DIGNITARY™

STONE ATTACHÉ™ COLLECTION – COLORBODY™ PORCELAIN

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 ♦ Floor Tile	(23-7/16" x 47-1/16") (59.50 cm x 119.50 cm)	7/16"	15.50	2
	24 x 24 ■ Paver Tile	(23-7/16" x 23-7/16") (59.50 cm x 59.50 cm)	13/16" (2cm)	7.76	2
	24 x 24 ♦ Floor Tile	(23-7/16" x 23-7/16") (59.44 cm x 59.44 cm)	3/8"	15.20	4
	12 x 24 Floor Tile	(11-11/16" x 23-7/16") (29.65 cm x 59.44 cm)	3/8"	15.12	8
	Abstract ♦ Mosaic (Mesh Mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	3/8"	3.88	4

- ♦ Available in Unpolished only
- Available in 2cm thickness with textured surface in DR07, DR08 and DR09 colors only

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓***
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓**




A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.


- * Unpolished and Textured only
- ** Mosaic tile only
- *** Textured only

TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	S-43F9	3 x 24	10
	Cove Base	S-36C9T	6 x 12	20
	Cove Base Outcorner	SC-36C9T	1 x 6	10

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Random (V4)
Mosaic: 1/8"	

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs > 1000 lbs (2cm)
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltillegreenworks.com.

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



IMAGINE WHAT'S POSSIBLE™

©2018 Daltille (4/18)