

SURETREAD SURFACE




Red OQ81 (1)



Wheat OQ79 (2)



Golden Brown OQ75 (2)




Bronze Clay OQ86 (2)




Gray OQ76 (2)



Storm Gray OQ82 (2)



Chocolate OQ88 (2)



Black OQ73 (2)

PAVER SURFACE



Red OQ84 (1)



Wheat OQ80 (2)



Golden Brown OQ78 (2)



Bronze Clay OQ87 (2)



Gray OQ85 (2)



Storm Gray OQ83 (2)



Chocolate OQ89 (2)



Black OQ74 (2)

(1) and (2) indicate price groups, (1) being the least expensive

Protect The Pep In Your Step

- **NATURAL RESISTANCE**
 - Available in a smooth paver surface and a textured tread surface
 - Durable, natural product with low moisture absorption
 - Textured surface provides excellent slip-resistance

- **COMMERCIAL APPEAL**
 - Withstands extreme amounts of weight such as kitchen equipment and auto displays
 - Tread surface prevents grease and water from building under feet
 - Quarry Guard makes it easier to clean and stain-resistant



**PRE-CONSUMER
RECYCLED MATERIALS**




MADE IN THE U.S.A.

All or select items within this series are made in the USA. For more information, visit daltile.com/SuretreadPavers.

SURETREAD™ & PAVERS™

with QUARRY GUARD™

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	6 x 6 Field Tile	(6" x 6") (15.20 cm x 15.20 cm)	3/8"	12.00	48

Sizing differences may exist between gray and red colors. When mixing colors, check actual samples to ensure sizing compatibility.

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓
Subject to Oils	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.daltile.com/dcof.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	✓






APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

QUARRY GUARD™

QUARRY GUARD™ IMPROVES THE GROUT RELEASE AND STAIN RESISTANCE OF THE TILE, RESULTING IN EASIER CLEAN-UP WITH INSTALLATION AND TILE THAT IS LESS LIKELY TO GET STAINED IN THE FUTURE.


TRIM

	Type	Number	Size	Pieces per Carton
	Bullnose	P-1665	6 x 6	48
	Bullnose Corner	PC-1665	6 x 6	26
	Cove Base	P-3665	6 x 6	48
	Cove Base Corner	PCR-L-3665	6 x 6	26
	Cove Base Inside Corner	PB-3665	3/4 x 6	50

Floor bullnose, cove base, and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

Suretread trim is a smooth trim. Tread surface is not available on trim.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 Medium (V2)

TEST RESULTS

	ASTM#	Floor
Water Absorption	C373	≤ 3.0%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™
CREDITS. For more detailed information,
visit daltilegreenworks.com.



SCAN QR CODE
FOR PRODUCT
INFORMATION

Get a QR Code
reader at:
GET.DAL TILE.COM



7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2015 Dal-Tile Corporation (12/15)